

Applicatifs(2)

■ Configurer named(bind) avec IPv6

- Pour activer IPv6, ajouter à named.conf la ligne suivante :

```
➤ listen-on-v6 { ::1 ; 2001:4f8:feec::1; }; or { any; };
```

■ Configurer Apache avec IPv6

- **/etc/httpd/conf/httpd.conf**

```
Listen [2001:4f8:feec::1]:80
```

```
NameVirtualHost [2001:4f8:feec::1]
```

```
<VirtualHost [2001:4f8:feec::1]:80>
```

```
DocumentRoot /var/www/html/trs
```

```
ServerName www.trstech.net
```

```
Errorlog logs/trstech.net-error_log
```

```
Customlog logs/trstech.net-access_log common
```

```
</VirtualHost>
```

Applications (3)

■ Configuration de radvd(radvd.conf)

```
interface eth0
{
  AdvSendAdvert on;
  MinRtrAdvInterval 3;
  MaxRtrAdvInterval 10;
  AdvHomeAgentFlag off;
  # example of a standard prefix
  prefix 2001:4f8:feec::/64
  {
    AdvOnLink on;
    AdvAutonomous on;
    AdvRouterAddr on;
    AdvPreferredLifetime 604800; # 7days
    AdvValidLifetime 259200; #30 days
  };
};
```

Applicatifs (4)

<http://www.ipv6-to-standard.org/>

Pour vérifier et renseigner

- **Le support IPv6 de vos applications**
- **Lour le support IPv6 de vos équipements**
- **Lour le support Ipv6 de vos fournisseurs**
- **Etc...**